Author(s) : F. Carminati
Library: KERNLIB, VAX/VMS only
Submitter :
Submitted: 01.03.1989
Language : VAX Fortran
Revised:

Usage Monitor for VAX/VMS

UMCOM is an usage monitor package for VAX/VMS systems. Usage log requests are performed either via Fortran calls or via DCL commands.

Structure:

Complete PROGRAM and SUBROUTINE subprograms
User Entry Names: UMCOM, UMLOG

Usage:

```
CALL UMCOM(CMD,MONITOR,TEXT)
```

CMD — (CHARACTER) The first two letters of CMD are interpreted as a command to UMON. See the **Long Write-up** for possible commands.

MONITOR — (CHARACTER) Name of the monitor to be affected by the command. If this name is longer than 8 characters, only the first 8 will be taken into account.

TEXT — (CHARACTER) A character string containing information about the command given. If this string is longer than 80 characters, only the first 80 will be taken into account.

```
CALL UMLOG(MONITOR,TEXT)
```

MONITOR — (CHARACTER) Name of the monitor to be affected by the command. If this name is longer than 8 characters, only the first 8 will be taken into account.

TEXT — (CHARACTER) A character string containing the text to be logged. If this string is longer than 80 characters, only the first 80 will be taken into account.

See also the **Long Write-up**.

•