Author(s) : F. Carminati, J. Zoll
Library: KERNLIB, VAX only
Submitter :
Submitted: 01.04.1994
Language : Fortran
Revised:

Get the name of the executing module

This routine will figure out the path-name of the executing image. On the VAX this is done with a system call, on UNIX by scanning the search path until it finds the module whose name is in `argv[0]`.

Structure:

`SUBROUTINE` subprograms
User Entry Names: `WHOAMI`
Common Blocks: `COMMON /SLATE/ ND,NE,NF,DUMMY(37)`

Usage:

```
    CALL WHOAMI(NAME)
```

On exit, `NAME` contains the full path-name of the module.
Status and various lengths are returned in `/SLATE/`:

```
    ND = 0  if the call failed,
       > 0  the number of characters in the path-name
```

On the VAX:

```
ND =  number of characters in the path-name with .EXE;n stripped
NE =  number of characters before the semicolon,
NF =  number of characters in the complete name.
```

For example:

```
      if NAME is  DISK:[CERN]WYLBUR.EXE;4
                  _:.=+=.: 1_:.=+=.: 2_:.=+=

      we will get  ND=17, NE=21, NF=23.
```

Note: At the moment this is available only on the VAX; the code exists for UNIX but is not yet in the library.

•